



Description

A durable 100% acrylic finish that can be used to create an almost endless variety of textured looks for interior and exterior walls ranging from smooth to heavy raised relief or made to resemble surfaces that include rustic stone or the appearance of an Old World Plaster finish.

Uses

Apply over properly prepared substrates that include flat concrete, stucco, masonry, high-quality plaster and interior gypsum board bases.

Advantages

- Easy to achieve texture effects
- Tintable to almost any color
- Suitable for interior or exterior applications
- Can be used with LaHabra Antiquing Gel

Packaging

5 gallon pails

Coverage

Coverage will vary depending on surface texture and porosity.

- Approximately 30 sq. ft. per gallon

Colors and Textures

Stucco d'Raffinato can produce a multitude of textures and colors.

Surface Preparation

- Surfaces must not be exposed to temperatures below 40° F for a 24-hour period prior to finish application.
- If used, a base coat must cure a minimum of 24 hours before applying Stucco d'Raffinato. (Note: Curing time may be longer in cool and/or humid climates)
- Surfaces must be unpainted, clean, dry, structurally sound and free from efflorescence, grease, oil, form release agents and curing compounds.
- Cure concrete at least 28 days before applying Stucco d'Raffinato. If curing compounds or form release agents are still present on the surface, wash it thoroughly with muriatic acid and then flush it to remove residual acids.
- Skim coat masonry surfaces with the joints struck flush, using a base coat to produce a smooth, level surface and allow it to cure at least 24 hours before applying Stucco d'Raffinato.
- Clean and level existing brick to form a smooth surface and allow it to cure for 24 hours before applying Stucco d'Raffinato.
- Interior drywall should be finished to a Level 3 finish.

Mixing

Read the entire label before using this product.

Although LaHabra Stucco d'Raffinato comes premixed, it is recommended that you stir it prior to application as the aggregate tends to settle during storage.

Application

LaHabra recommends that the project owner or designer approve a job site mock-up of the application of this product. The mock-up should demonstrate the products' appearance under the conditions given by the project specification(s).

1. A variety of application tools and techniques can be used, however, the most common involve the use of a metal trowel and spatula.
2. To apply Stucco d'Raffinato, use a stainless steel trowel to lay down a coat slightly thicker than 1/16". Texture can be created by dragging the trowel or other tool(s).

3. Allow the surface to dry for 15 minutes. Then using moderate pressure, use a plastic float to smooth out some of the heavy texture.
4. Texture can be created – as well as designs – by using various tools.
5. Allow the surface to dry completely.
6. At this stage, an Old World Plaster finish can be created by glazing and/or staining the product.

Clean Up

Clean tools frequently using clean water.

Maintenance

LaHabra Stucco d'Raffinato can be cleaned with a soap and water solution followed by a warm water rinse. Do not use harsh or abrasive cleaners.

Storage and Handling

Transport and store Stucco d'Raffinato in closed, undamaged containers. DO NOT ALLOW TO FREEZE.

Shelf Life

If the product remains in an unopened, undamaged, original sealed pail that is properly transported and stored, Stucco d'Raffinato has a shelf life of up to 1 year.

Cautions and Limitations

- In case of contact with eyes, flush with clean water and seek medical attention if irritation persists.
- Use only on surfaces that are sound, clean, dry, unpainted, and free from any residue that might affect the ability of this product to bond to the surface.
- Ambient and surface temperature must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Avoid application in direct sunlight in hot weather.
- Do not allow to freeze until completely dry.

Corporate Office

ParexLaHabra, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
Telephone: 714-778-2266
Toll Free: 877-LHSTUCCO
Fax: 714-774-2079

Plants

Riverside, CA
French Camp, CA
Albuquerque, NM
Colorado Springs, CO
San Antonio, TX
Redan, GA
Wilkes Barre, PA

Warehouses

Anaheim, CA
North Hollywood, CA

