

LaHabra® Exterior Fast Patch

LaHabra® Exterior Fast Patch is an easy to use, non-shrinking patch for exterior plaster. This material is QUICK SETTING and should be used within 15-20 minutes after mixing.



LaHabra

LaHabra® Exterior Fast Patch

Architectural Specification Guide



Description

- A. LaHabra Exterior Fast Patch is designed as an easy to use, non-shrinking patch for exterior plaster. This material is QUICK SETTING and should be used within 15 to 20 minutes.

Coverage

Varies with thickness, approximately 8-10 sq. ft. (.75-1m²) per 40 lb. bag at 1/2 inch thickness.

Packaging

Product is available in 40 lb. paper bags.

Job Procedure

- A. Mixing:
Material should be thoroughly mixed with clean water to a trowelable consistency.
- B. Application:
The area to be patched should be dampened before patching. Small holes may be patched in one step. Large holes should be done in two steps with a scratch coat followed with a finish coat after the scratch coat takes up.

Cautions and Limitations

- A. Material should not be retempered.
- B. See package for handling precautions.
- C. Always wear proper safety equipment, including particle mask, when mixing and/or applying this product.



LaHabra

Corporate Office

ParexLaHabra, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
Telephone: 714-778-2266
Toll Free: 877-LHSTUCCO
Fax: 714-774-2079

Plants

Riverside, CA
French Camp, CA
Albuquerque, NM
Colorado Springs, CO
San Antonio, TX
Redan, GA
Wilkes Barre, PA

Warehouses

Anaheim, CA
North Hollywood, CA



Email: info@lahabrastucco.com
lahabrastucco.com