

DPR Coating

Acrylic Coating



DPR Coating

DESCRIPTION:

- 100% Acrylic-based coating available in textured or non-textured
- DPR (Dirt Pick-up Resistance): The surface of the coating hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold, and pollutants
- Excellent hiding power as well as flexibility and drying characteristics
- Mixed on site with water
- Integrally colored with high quality pigments

USES:

- A protective and decorative exterior or interior coating over concrete, masonry, stucco, or acrylic-based textured finishes. Compatible with Parex USA finishes, may be applied over them
- To promote color uniformity of repaired and modified surfaces
- To color architectural details and graphics on any of the Parex USA Finishes and Coatings.
- Recoating existing EIFS or Stucco

COMPOSITION:

- Binder Base: 100% Acrylic
- Color: White or tinted to desired color
- Pigment based: Titanium dioxide
- Water base: VOC-Compliant

PROPERTIES:

- Appearance: Flat, non-gloss, smooth finish
- Vapor Permeability: Water vapor permeable. Does not create a vapor barrier

100% Acrylic
+DPR

PAREXUSA

COVERAGE:

Depending on the condition of the substrate and method of application, approximate coverages are:

- DPR Coating
One coat: 1000-1200 sq. ft.
(93-112 sq. m.) / pail

CONTAINER:

60 lb (27.7kg) net weight in plastic pails.

- Storage: Protect from direct sunlight and freezing at all times
- Do not stack pails more than 3 pails high
- Shelf Life: One year if properly stored.

DRYING TIME:

Approximately 1-4 hours depending upon temperature, humidity and substrate. Can be recoated after 8 hours. Allow minimum 5 days curing before gently washing the surface.

CLEAN-UP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Remove surface contaminants such as dust or dirt without damaging the substrate.
- For previously painted surfaces, all loose and chalking paint must be removed, and glossy surfaces dulled.
- New concrete and masonry must be clean and cured a minimum of 28 days.
- Check concrete surfaces for alkalinity and treat. Any form-release agents or bond breakers must be removed.
- Uneven concrete or masonry can be leveled with any Parex USA Base Coat & Adhesive or other suitable, compatible product.

- For interior drywall, prepare as for painting.
- Prime cementitious surfaces with any Parex USA Primer.
- For application of specific Parex USA Primers refer to the Product Data Sheet.
- For additional options, contact Parex USA Technical Support.

MIXING:

- Use clean equipment for mixing and preparation
- Stir DPR Coating to a uniform consistency.
- Avoid creating air bubbles or foam.
- Stir occasionally as needed to keep uniformly mixed.

APPLICATION:

- Read the entire label before using this product
- Parex USA DPR Coating exhibits good surface coverage in single application. However, for most uncoated, unprimed surface of concrete, masonry, or drywall, two coats of the product may be required to obtain adequate hiding of the substrate and best performance.
- Parex USA DPR Coating is easily applied with either brush, roller, or suitable spray equipment. Apply as packaged. If necessary, add a small amount of clean potable water: maximum 8 oz (0.25L) / pail.
- Add the same amount of water to each bucket. Also if different batches are used on the job box them for best color consistency

LIMITATIONS:

- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Use only on surfaces that are sound, clean, dry, and free from any residue which may affect the ability of the DPR Coating to bond to the surface.
- Application in direct sunlight in hot weather may adversely affect aesthetics.

WARNING

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- For more information on handling this product refer to its Material Safety Data Sheet (MSDS). The most current MSDS and Product Data Sheet (PDS) can be found on our website.
- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

PAREXUSA
www.parexusa.com

Corporate Office

Parex USA, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
(866) 516-0061
Tech Support: (800) 226-2424

Facilities

Redan, GA
Riverside, CA
French Camp, CA
Colorado Springs, CO
Albuquerque, NM
San Antonio, TX
Wilkes Barre, PA
Ft. Pierce, FL

