

PAREXUSA

Quik Cure



DESCRIPTION:

- Water-based acrylic curing membrane formulated to provide excellent performance in the water retention section of ASTM C 309.
- Provides a curing membrane over cementitious surfaces allowing acrylic finishes to be applied quickly, while protecting against delamination and efflorescence.
- Provides a sound, sealed substrate for a uniform finish over either stucco or concrete.

COVERAGE:

900-1,200 sq. ft. (84-111 sq. m)/5 gallon pail depending on the porosity of the stucco base.

USES:

Recommended as a surface preparation for stucco, masonry, drywall, plaster, concrete tilt wall and concrete poured in place.

STORAGE:

Protect from sun and freezing at all times.

DRYING TIME:

Dependent upon air temperature and relative humidity. Under average drying conditions 70°F (21°C), 55% R.H., Quik Cure will dry to touch in 1/2 hour and be sufficiently dry for application of finish in 2 hours.

CLEAN-UP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Substrate must be clean. Remove all foreign matter, alkali deposits, oil, dirt, etc.
- For additional options, contact Parex USA Technical Support.

MIXING:

Stir very slowly to ensure a smooth, homogenous consistency.

APPLICATION:

Can be applied using a brush, roller, airless sprayer or pump up garden sprayer.

LIMITATIONS:

- Ambient and surface temperature must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Avoid application in direct sunlight in hot weather.
- Quik Cure is not to be used as an admixture. (Use Teifs Admix).

WARNING

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- For more information on handling this product refer to its Material Safety Data Sheet (MSDS). The most current MSDS and Product Data Sheet (PDS) can be found on our website.
- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

PAREXUSA
www.parexusa.com

Corporate Office

Parex USA, Inc.
4125 E. La Palma Ave., Suite 250
Anaheim, CA 92807
(866) 516-0061
Tech Support: (800) 226-2424

Facilities

Redan, GA
Riverside, CA
French Camp, CA
Colorado Springs, CO
Albuquerque, NM
San Antonio, TX
Wilkes Barre, PA
Ft. Pierce, FL

