

# SAFETY DATA SHEET PU COLORFAST KX

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

**Product identifier** 

Product name PU COLORFAST KX

Product number 8517

Internal identification WHITE

Recommended use of the chemical and restrictions on use

Application Pigment

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Manufacturer ParexUSA, Inc.

4125 E. La Palma Ave, Suite 250 Anaheim, CA 92807, USA

T: 1-800-226-2424 F: 1-714-774-2079

Contact Information Technical Department

technicalservice@parexusa.com

www.parexusa.com

Emergency telephone number

Emergency telephone CHEMTREC

1-800-424-9300

#### 2. Hazard(s) identification

#### Classification of the substance or mixture

Physical hazards Not Classified

**Health hazards** Eye Irrit. 2A - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

Label elements

Pictogram



Signal word Warning

**Hazard statements** H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

# PU COLORFAST KX

**Precautionary statements** P261 Avoid breathing vapor/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with national regulations.

# Contains 3-iodo-2-propynl-butylcarbamate

#### Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### 3. Composition/information on ingredients

#### **Mixtures**

CAS number: 13463-67-7

# Classification Not Classified

Aluminum Hydroxide 1-5%

CAS number: 21645-51-2

#### Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

STOT SE 3 - H335

#### Isoalcohols, C-13-Rich, Ethoxylated

1-5%

CAS number: 78330-21-9

#### Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411

#### PU COLORFAST KX

3-iodo-2-propynl-butylcarbamate <1%

CAS number: 55406-53-6

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Acute Tox. 4 - H302 Acute Tox. 3 - H331 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT RE 1 - H372 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### 4. First-aid measures

#### Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery

position and ensure breathing can take place.

**Ingestion** Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if

the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical

attention.

**Skin Contact** Rinse with water.

Eye contact Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart.

Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

#### Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Irritation of nose, throat and

airway. Difficulty in breathing. Coughing. Prolonged or repeated exposure may cause the

following adverse effects: Suspected of causing cancer.

Ingestion May cause irritation. Prolonged or repeated exposure may cause the following adverse

effects: Suspected of causing cancer.

**Skin contact** Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse

effects: Suspected of causing cancer.

**Eye contact** Irritating to eyes.

#### Indication of immediate medical attention and special treatment needed

#### PU COLORFAST KX

Notes for the doctor Treat symptomatically.

# 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

Containers can burst violently or explode when heated, due to excessive pressure build-up. Specific hazards

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

# Advice for firefighters

# Protective actions during

firefighting

Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

# Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be

taken without appropriate training or involving any personal risk. Avoid inhalation of dust and

vapors. Use suitable respiratory protection if ventilation is inadequate.

**Environmental precautions** 

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the

aquatic environment.

# Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills

> immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do

not empty into drains. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

# 7. Handling and storage

#### PU COLORFAST KX

#### Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

> Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse

empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash

before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store locked up. Keep only in the original container. Keep container tightly closed, in a cool,

well ventilated place. Keep containers upright. Protect containers from damage.

Miscellaneous hazardous material storage. Storage class

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

#### 8. Exposure Controls/personal protection

# Control parameters

#### Occupational exposure limits

#### **Titanium Dioxide**

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen. OSHA = Occupational Safety and Health Administration.

Titanium Dioxide (CAS: 13463-67-7)

Immediate danger to life

and health

5000 mg/m<sup>3</sup>

Silicon Dioxide (CAS: 7631-86-9)

Immediate danger to life and health

3000 mg/m<sup>3</sup>

# **Exposure controls**

#### Protective equipment







Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-

face respirator may be required instead.

#### PU COLORFAST KX

Hand protection Wear protective gloves. The most suitable glove should be chosen in consultation with the

glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash hands thoroughly after handling. Wash at the end of each work shift and before eating,

smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

Environmental exposure

controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance Liquid.

Odor threshold No information available.

PH No information available.

Melting point Not available.

**Initial boiling point and range** No information available.

Flash point No information available.

**Evaporation rate** No information available.

Flammability (solid, gas) No information available.

Upper/lower flammability or

**Auto-ignition temperature** 

explosive limits

Solubility(ies)

No information available.

Insoluble in water.

No information available.

Vapor pressureNo information available.Vapor densityNo information available.Relative densityNo information available.

to mornator available

Partition coefficient No information available.

**Decomposition Temperature** No information available.

Viscosity No information available.

Other information None.

#### PU COLORFAST KX

10. Stability and reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

## 11. Toxicological information

# Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅) Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 28,571.43

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 545.45

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Suspected of causing cancer.

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

# PU COLORFAST KX

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335 May cause respiratory irritation.

Target organs Respiratory system, lungs

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

General information May cause cancer after repeated exposure. Risk of cancer depends on duration and level of

exposure. The severity of the symptoms described will vary dependent on the concentration

and the length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Irritation of nose, throat and

airway. Difficulty in breathing. Coughing.

**Ingestion** May cause irritation.

**Skin Contact** Redness. Irritating to skin.

Eye contact Irritating to eyes.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target Organs Respiratory system, lungs

### 12. Ecological Information

**Toxicity** Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

Partition coefficient No information available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

# 13. Disposal considerations

#### Waste treatment methods

**General information** The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

# PU COLORFAST KX

**Disposal methods**Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.

Incineration or landfill should only be considered when recycling is not feasible.

#### 14. Transport information

**UN Number** 

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

**DOT transport labels** 

No transport warning sign required.

Packing group

**DOT packing group**Not applicable.

Special precautions for user

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

#### 15. Regulatory information

# **US Federal Regulations**

# SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

# CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

# SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

# SARA 313 Emission Reporting

The following ingredients are listed or exempt:

3-iodo-2-propynl-butylcarbamate

1.0 %

#### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

#### FDA - Essential Chemical

None of the ingredients are listed or exempt.

#### FDA - Precursor Chemical

None of the ingredients are listed or exempt.

#### SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

# **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

# PU COLORFAST KX

# **US State Regulations**

#### California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

#### California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

# California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

#### California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

#### Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

#### Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

#### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

#### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

3-iodo-2-propynl-butylcarbamate

Present.

#### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

#### Inventories

# US - TSCA

The following ingredients are listed or exempt:

3-iodo-2-propynl-butylcarbamate

Present.

2-methylisothiazol-3(2H)-one

Present.

# US - TSCA 12(b) Export Notification

The following ingredients are listed or exempt:

2-methylisothiazol-3(2H)-one

Present.

# 16. Other information

**Training advice** Only trained personnel should use this material.

Revision date 8/20/2018

Revision 1

**SDS No.** 4778

# PU COLORFAST KX

Hazard statements in full H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.